



US011110896B2

(12) **United States Patent**
Dalal

(10) **Patent No.:** **US 11,110,896 B2**

(45) **Date of Patent:** **Sep. 7, 2021**

(54) **PULSED LASER CLEANING OF DEBRIS
ACCUMULATED ON GLASS ARTICLES IN
VEHICLES AND PHOTOVOLTAIC
ASSEMBLIES**

(71) Applicant: **TESLA, INC.**, Palo Alto, CA (US)

(72) Inventor: **Phiroze Dalal**, San Jose, CA (US)

(73) Assignee: **Tesla, Inc.**, Palo Alto, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/408,671**

(22) Filed: **May 10, 2019**

(65) **Prior Publication Data**

US 2019/0351873 A1 Nov. 21, 2019

Related U.S. Application Data

(60) Provisional application No. 62/672,251, filed on May 16, 2018.

(51) **Int. Cl.**

B60S 1/02 (2006.01)
B23K 26/16 (2006.01)
B23K 26/36 (2014.01)
B60R 11/04 (2006.01)
B08B 7/00 (2006.01)
B60R 11/00 (2006.01)

(52) **U.S. Cl.**

CPC **B60S 1/02** (2013.01); **B08B 7/0042** (2013.01); **B60R 11/04** (2013.01); **B60R 2011/0005** (2013.01)

(58) **Field of Classification Search**

CPC B60S 1/02-026; B23K 26/0006; B23K 26/02-043; B23K 26/16; B23K 26/36-361

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,720,621 A * 1/1988 Langen B23K 26/03 219/121.6
5,151,134 A * 9/1992 Boquillon B08B 7/0042 134/1

(Continued)

OTHER PUBLICATIONS

English translation of CN 11361527 (Year: 2020).*

English translation of CN 105459968 (Year: 2016).*

Primary Examiner — Michael A Laflame, Jr.

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson & Bear, LLP

(57)

ABSTRACT

A cleaning system for a vehicle includes a beam optics assembly that emits a laser beam to irradiate a region on a glass article of the vehicle, debris detection circuitry that detects debris accumulated over the region, and control circuitry. The control circuitry calibrates a set of parameters associated with the laser beam emitted from the beam optics assembly based on detection of the debris accumulated over the region on the glass article, controls an exposure level of the laser beam on the debris accumulated based on calibration of the set of parameters associated with the laser beam, wherein the exposure level is controlled based on pulsing the laser beam at a calibrated rate that limits penetration of the laser beam to a depth that is less than a thickness of the glass article, and removes the debris accumulated over the region on the glass article using the laser beam.

10 Claims, 5 Drawing Sheets

